



Equipment - Screenshot 2024-06-26 152553.png

1. Technical data

1. Technical data

Boltec MC and MD

Note
A brief summary of data follows. For more detailed information, see the maintenance instructions.

Length	12.5-13.5m
Width	2.21m excl. bolt rack
Height, rig with protective roof	2.27-2.97m
Height, rig with cab, std	3.00m
Height, rig with cab, option	2.80-3.25m
Weight	See data plate
Installed diesel engine power	115kW
Installed electric power capacity	See data plate
Voltage	See data plate
Frequency	See data plate
Max. lateral inclination	0°
Max. longitudinal inclination.	14°
Stability	Complies with CEN
Ambient temperature	0 to +40°C
Noise level at operator's station (ISO/DIS 11201)	80dB(A) re2 µPa
Radiated acoustic power (ISO/DIS 11201)	121.9dB(A) re1 pW
Vibration level, floor (ISO 2631/1)	0.09m/s ²

Boltec LC and LD

Note
A brief summary of data follows. For more detailed information, see the maintenance instructions.

Length (depending on boom type and feeder type)	14.5-16.6m
Width, standard	2.5 m
Height, rig with protective roof	2.4-3.1m
Height, rig with cab, std	3.1m
Height, rig with cab, option	2.90-3.35m
Weight	See data plate
Installed diesel engine power	115kW
Installed electric power capacity	See data plate