

MOTOR SPECIFICATIONS

Motor Design	NEMA design B, squirrel cage induction, air filled
Motor Type	Enclosed submersible, IP 68
Maximum submergence	65 feet (20m)
Insulation Class	Class F, rated at 155° C
Motor Protection	Bi-metallic Thermal Switch
Bi-Metallic Temp Trip	130° C ± 5° C
Service Factor	1.15
Max. Liquid Temperature	104°F (40°C)
Voltage Tolerance	± 10% from nominal
MSHA Approval	2G-2796 (230V), 2G-2796A (460V), 2G-2796A-1(575V)



MOTOR DATA, 60Hz

Model	Phase	Output Power BHP	Volts	Full Load Amps	Locked Rotor Amps	NEMA Code Letter	Power Factor 100% Load	Motor Efficiency 100% Load	Pole/Speed (rpm)
P40CE	3	6.4	230	17.8	122.6	J	.76	.80	2/3450
			460	8.9	61.3	J	.76	.80	2/3450
			575	8.6	49	J	.76	.80	2/3450

MATERIALS OF CONSTRUCTION

Material	Standard	High chrome
Upper Motor Lid	356-T6 Aluminum	356-T6 Aluminum
Motor Housing	356-T6 Aluminum	356-T6 Aluminum
Lower Seal Housing	AISI 304 Stainless Steel	ASTM A532 Class III Type Chromium
Volute	356-T6 Aluminum - Rubber Lined	356-T6 Aluminum - Polyurethane Lined
External Hardware	AISI 304 Stainless Steel	AISI 304 Stainless Steel
O-Rings	NBR	NBR
Motor Shaft	AISI 416 Stainless Steel	AISI 416 Stainless Steel
Upper Bearing	Deep groove ball bearing, double sealed	Deep groove ball bearing, double shielded
Lower Bearing	Double row angular contact ball bearing, double shielded	Double row angular contact ball bearing, double shielded
Shaft Seal	SiC/SiC	SiC/SiC
Impeller	AISI 316 Stainless Steel	ASTM A532 Class III Type Chromium

DIMENSIONS, WEIGHT, AND MISC.

Pump weight (without cable)	87 lbs (39.5kg)
Discharge size, HH	3 inch NPT male vertical
Discharge size, HV	4 inch NPT male vertical
Strainer Opening	9mmX22mm

CABLE SPECIFICATIONS

MODEL	PHASE/VOLTAGE	POWER CABLE *	LENGTH *	OUTER JACKET
P40CE	3Ø-230V	Drill Cord SOOW 12/5, 10/5. 8/3G-GC	Per MSHA Approval	CPE, Heavy Duty
	3Ø-460V	Drill Cord SOOW 12/5, 10/5. 8/3G-GC	Per MSHA Approval	CPE, Heavy Duty
	3Ø-575V	Drill Cord SOOW 12/5, 10/5. 8/3G-GC	Per MSHA Approval	CPE, Heavy Duty

* Cable size and length per MSHA approval.






PERFORMANCE CURVE

Mine Dewatering Pumps P40CE HH

Dwg: DS-A16-013 Rev: 5 Date: 8/29/2017




Pump Performance Test - US Units

Test Standard : HI 11.6 Gr 3B
Tested with water at 20°C
Frequency 60 Hz
Pump Speed 3450 RPM
Impeller Ø160mm

Specifications subject to change without notice

Dwg: DS-A16-015 Rev: 4 Date: 11/7/2016



Pump Performance Test - Metric Units

Test Standard : HI 11.6 Gr 3B
 Tested with water at 20°C
 Frequency 60 Hz
 Pump Speed 3450 RPM
 Impeller Ø135mm

Specifications subject to change without notice