


VERSATILE FULLY MECHANIZED BOLTER



COMPACT
EASY TO HANDLE
POWERFUL
LARGE BOOM COVERAGE
HIGH BOLTING PERFORMANCE
THC BOLTING SYSTEM
EASY MAINTENANCE
THREE VERSIONS










ROBOH 05

EASY TO HANDLE





POWERFUL

- 45 kW electro-hydraulic power pack
- IP 55 protection class
- > 1000 V system available
- 100 m capacity electric cable reel (cable OD=32 mm)
- > 440 W working light power
- EN (Eur), UL (USA), CSA (Can), AS (Aus) models available
 Local standards and regulations covered





LARGE BOOM COVERAGE

B 26 XL B BOOM

Installation of several rows of bolts without moving the machine
Robust boom support
Stiff and strong rectangular profile
Adjustable pins at all boom joints
Large capacity hydraulic system
1.7 m boom extension













LARGE BOOM COVERAGE




















ROBOTIOS

HIGH BOLTING PERFORMANCE

Expansion Resin



Drilling Line Hydrastar 200

Bolting Line RHR 50

Cement



Drilling Line Hydrastar 200

Bolting Line
Pusher
(or RHR 50)

Split Set



Drilling Line Hydrastar 200

Bolting Line
HH 200 impactor
(or Hydrastar 200)

Swellex



Drilling Line Hydrastar 200

Bolting Line
Water Intensifier
(+ RHR 50)

Pure Rotary



Drilling Line RHR 50

Bolting Line RHR 50



TAMIROCK



ROBOH 05

THC DRILLING SYSTEM

POWERFUL AND RELIABLE HYDRAULICS



45 Kw Power Pack

- •1 variable displacement pump for percussion, bolting head and boom.
- •1 gear pump for rotation.

THC 560 B

- Optimal drilling parameters.
- Accurate smooth collaring.
- Ergonomic design.
- Logical layout.







EASY MAINTENANCE

Rock Drill

 Modules can be changed and serviced on bolting head beam.

Visual wear indicators

THC

Regulating drilling and bolting operations.

Boom

•Wearing pieces can be changed without dismantling the boom.

•Wear can be taken up by conical cylinder pins.










THREE VERSIONS

1 . BULK CEMENT











THREE VERSIONS

BULK CEMENT



With the Robolt 06 cement mixer and pump, the water to cement ratio can be low (0.3-0.35) and grouting mass pumping is started from the bottom of the hole.

For cleaning the bolting head, a high pressure washing system is available in option.









THREE VERSIONS

2. SCREEN HANDLER












THREE VERSIONS

SCREEN HANDLER



Only one operator can operate the bolting boom and the screen handler boom from the control station.







THREE VERSIONS

3. BASKET BOOM














THREE VERSIONS

BASKET BOOM











AND NOW ...

EVERYTHING YOU WANTED TO KNOW ABOUT BOLTING BUT WERE AFRAID TO ASK



