General Model Specifications:

Capacities:

- Tramming Capacity: 2,722 kgs (6,000 lbs)
- Hydraulic Breakout Force Lift: 6,043 kgs (13,322 lbs)
- Hydraulic Breakout Force Tilt: 5,372 kgs (11,844 lbs)
- SAE breakout force: 4,735 kgs (10,441 lbs)
- SAE static Tipping Load: 9,662 kgs (21,301 lbs)
- Bucket: 1.5yd³ (1.2m³)

Overall Dimensions

- Tramming Length: 6,365mm (20ft 10.5in)
- Width Overall: 1,514mm (4ft 11.5in)
- Height (Canopy): 1,935 mm (6ft 4in) Length:
- Rear Axle to Bumper: 2,288mm (7ft 6in)
- Centre Hinge to Rear Axle: 1,041mm (3ft 5in)
- Centre Hinge to Front Axle: 1,045mm (3ft 5in)
- Reach: 1,218mm (4ft)
- Height (Top of Hood): 1,493mm (4ft 10.75in)

- Height Ground Clearance: 204mm (8in)
- Height Dump Clearance: 1,111mm (3ft 7.5in)
- Height Bucket Pin: 2,075mm (6ft 10in)
- Height Bucket Raised: 3,266mm (10ft 8.5in)
- Maximum Width RF: 1,422mm (4ft 8in)
- Outside Radius: 4,374mm (14ft 4in)
- Inside Radius: 2,380mm (6ft 17.75in)
- Turn Angle: 37° Degrees
- Dump Angle: 38° Degrees
- Roll Back Angle: 50° Degrees